


Fibre optic diffuse reflection sensor

FT-00-P-V-E1



Application

Function principle	Diffuse reflection sensor
Application	For use in industrial environments

Detection zone

Range with fibre optic amplifier type	OCF; OKF; OOF; OUF
---------------------------------------	--------------------

OCF (High Power)

Range fibre optics [mm]	40
-------------------------	----

OKF

Range fibre optics [mm]	8
-------------------------	---

OOF

Range fibre optics [mm]	24
-------------------------	----

OUF

Range fibre optics [mm]	8
-------------------------	---

Operating conditions

Ambient temperature [°C]	-20...80
--------------------------	----------

Mechanical data

Weight [g]	37.5
Version of sensing head	straight
Sensing head diameter [mm]	1

E20053



Fibre optic diffuse reflection sensor

FT-00-P-V-E1

Sensing head length	[mm]	5
Total length	[mm]	600
Min. bending radius	[mm]	20
Fibre arrangement		⓪
Materials		Adapter: PPE
Fibre material		glass
Fibre head material		stainless steel (1.4305 / 303)
Fibre sheath material		PVC

Accessories

Items supplied	Mounting clamp:, E20107
----------------	-------------------------

Remarks

Pack quantity	1 pcs.
---------------	--------