


MN207S



Magnetically coded sensor

MN14005-AKOG/LJ0.1m/-H/US



- 1 sensor
- 2 coded target
- 3 illustration (example)



Product characteristics	
Output function	2 x normally open; (potential-free)
Sensing range [mm]	5; (with defined actuator)
Housing	rectangular
Dimensions [mm]	36 x 13 x 26
Application	
Design	coded target
Type of operation	permanent operation
Electrical data	
Operating voltage [V]	24 DC; ("supply class 2" to cULus)
Rated insulation voltage [V]	60
Protection class	III
Reverse polarity protection	no
Internal resistance (Ri) [Ω]	10; (1 W)
Outputs	
Output function	2 x normally open; (potential-free)
Permanent current rating of switching output DC [mA]	50
Switching frequency DC [Hz]	150
Output data	Interface type A
Short-circuit proof	no
Max. capacitive load CL_max [nF]	20
Detection zone	
Sensing range [mm]	5; (with defined actuator)

MN207S



Magnetically coded sensor

MN14005-AKOG/LJ0.1m/-H/US

Safe switching-off distance s(ar)	[mm]	15
--------------------------------------	------	----

Response times

Response time to safety request	[ms]	10
Max. fall time	[ms]	0.1
Max. make time incl. bounce	[ms]	0.6

Operating conditions

Applications	class C to EN 60654-1 weatherproof application	
Ambient temperature	[°C]	-25...80
Note on ambient temperature	operational life ≤ 87600 h	
Ambient temperature	[°C]	10...40
Note on ambient temperature	operational life ≤ 175200 h	
Max. relative air humidity	[%]	briefly: 5...95 %; permanent: 5...70 %
Air pressure	[kPa]	80...106
Max. height above sea level	[m]	2000
Salt spray	no	
Protection	IP 67; IP 69K; (protected cable laying)	

Tests / approvals

EMC	IEC 60947-5-1	
Shock resistance	EN 60068-2-27	30 g (11 ms)
Vibration resistance	IEC 60068-2-6	10 g (10...55 Hz)
UL approval	Enclosure type	Type 1, 4x, "for indoor use only", 12
	power supply	Class 2
	File number UL	E174191

Safety classification

Mission time TM	[h]	≤ 175200
Mission time TM (additional indication)	20 years	
B10D	20.000.000; (without load; at max. load DC 12, 24 V, 50 mA: 400.000)	

Mechanical data

Weight	[g]	130.5
Housing	rectangular	
Mounting	non-flush mountable	
Dimensions	[mm]	36 x 13 x 26
Materials	PA	
Tightening torque	[Nm]	0.8...2

Accessories

Items supplied	coded target	
----------------	--------------	--

Remarks

Remarks	In connection with a G150xS / AC4x2S type evaluation unit, it is possible to reach up to PL e (ISO 13849-1) or SIL cl 3 (IEC 62061)	
Pack quantity	1 pcs.	

MN207S



Magnetically coded sensor

MN14005-AKOG/LJ/0.1m/-H/US

Electrical connection - plug

Cable: 0.1 m, PVC, Ø 5 mm

Connector: 1 x M12; coding: A



Connection

